

# **SAFETY SYSTEMS FOR POWER EQUIPMENT**

## Cross-Reference to Related Applications

This application is a continuation of U.S. Patent Application Serial No.  
5 10/215,929, filed August 9, 2002, which claims the benefit of and priority from U.S.  
Provisional Patent Application Serial No. 60/312,141, filed August 13, 2001. Both of the  
above applications are hereby incorporated by reference in their entirety for all purposes.

## Background

Beginning with the industrial revolution and continuing to the present, mechanized  
10 equipment has allowed workers to produce goods with greater speed and less effort than  
possible with manually-powered tools. Unfortunately, the power and high operating  
speeds of mechanized equipment creates a risk for those operating such machinery. Each  
year thousands of people are maimed or killed by accidents involving power equipment.

As might be expected, many systems have been developed to minimize the risk of  
15 injury when using power equipment. Probably the most common safety feature is a guard  
that physically blocks an operator from making contact with dangerous components of  
machinery, such as belts, shafts or blades. In many cases, guards are effective to reduce  
the risk of injury, however, there are many instances where the nature of the operations to  
be performed precludes using a guard that completely blocks access to hazardous  
20 machine parts.

Various systems have been proposed to prevent accidental injury where guards  
cannot effectively be employed. For instance, U.S. Patent Nos. 941,726, 2,978,084,

3,011,610, 3,047,116, 4,195,722 and 4,321,841, the disclosures of which are incorporated herein by reference, all disclose safety systems for use with power presses. These systems utilize cables attached to the wrists of the operator that either pull back a user's hands from the work zone upon operation or prevent operation until the user's hands are outside  
5 the danger zone. U.S. Patent Nos. 3,953,770, 4,075,961, 4,470,046, 4,532,501 and 5,212,621, the disclosures of which are incorporated herein by reference, disclose radio-frequency safety systems which utilize radio-frequency signals to detect the presence of a user's hand in a dangerous area of the machine and thereupon prevent or interrupt operation of the machine.

10 U.S. Patent Nos. 4,959,909, 5,025,175, 5,122,091, 5,198,702, 5,201,684, 5,272,946, and 5,510,685 disclose safety systems for use with meat-skinning equipment, and are incorporated herein by reference. These systems interrupt or reverse power to the motor, or disengage a clutch, upon contact with a user's hand by any dangerous portion of the machine. Typically, contact between the user and the machine is detected by  
15 monitoring for electrical contact between a fine wire mesh in a glove worn by the user and some metal component in the dangerous area of the machine. Although such systems are suitable for use with meat skinning machines, they are relatively slow to stop the motion of the cutting element because they rely on the operation of solenoids or must overcome the inertia of the motor. However, because these systems operate at relatively  
20 low speeds, the blade does not need to be stopped rapidly to prevent serious injury to the user.

U.S. Patent Nos. 3,785,230 and 4,026,177, the disclosures of which are herein incorporated by reference, disclose a safety system for use on circular saws to stop the blade when a user's hand approaches the blade. The system uses the blade as an antenna in an electromagnetic proximity detector to detect the approach of a user's hand prior to  
5 actual contact with the blade. Upon detection of a user's hand, the system engages a brake using a standard solenoid. Unfortunately, such a system is prone to false triggers and is relatively slow acting because of the solenoid. U.S. Patent No. 4,117,752, which is herein incorporated by reference, discloses a similar braking system for use with a band saw, where the brake is triggered by actual contact between the user's hand and the blade.  
10 However, the system described for detecting blade contact does not appear to be functional to accurately and reliably detect contact. Furthermore, the system relies on standard electromagnetic brakes operating off of line voltage to stop the blade and pulleys of the band saw. It is believed that such brakes would take 50ms-1s to stop the blade. Therefore, the system is too slow to stop the blade quickly enough to avoid serious  
15 injury.

None of these existing systems have operated with sufficient speed and/or reliability to prevent serious injury with many types of commonly used power tools. Although proximity-type sensors can be used with some equipment to increase the time available to stop the moving pieces, in many cases the user's hands must be brought into  
20 relatively close proximity to the cutting element in the normal course of operation. For example, many types of woodworking equipment require that the user's hands pass relatively close to the cutting tools. As a result, existing proximity-type sensors, which

are relatively imprecise, have not proven effective with this type of equipment. Even where proximity sensors are practical, existing brake systems have not operated quickly enough to prevent serious injury in many cases.

In equipment where proximity-type detection have not proven effective, the cutting tool must stop very quickly in the event of user contact to avoid serious injury. By way of example, a user may feed a piece of wood through a table saw at a rate of approximately one foot per second. Assuming an average reaction time of approximately one-tenth of a second, the hand may have moved well over an inch before the user even detects the contact. This distance is more than sufficient to result in the loss of several digits, severing of vital vessels and tendons, or even complete severing of a hand. If a brake is triggered immediately upon contact with the saw's blade, the blade must be stopped within approximately one-hundredth of a second to limit the depth of injury to one-eighth of an inch. Standard solenoids or other electromagnetic devices are generally not designed to act in this time scale, particularly where significant force must be generated. For instance, in the case of solenoids or electromagnetic brakes that operate on 60hz electrical power, it is possible that the power line will be at a phase that has low voltage at the time the brake is triggered and several milliseconds may elapse before the voltage reaches a sufficient level even to begin physical displacement of the brake, much less achieve a complete stoppage of the blade or cutting tool.

#### Brief Description of the Drawings

Fig. 1 is a schematic block diagram of a machine with a fast-acting safety system according to the present invention.

Fig. 2 is a schematic diagram of an exemplary safety system in the context of a machine having a circular blade.

### Detailed Description

A machine according to the present invention is shown schematically in Fig. 1 and indicated generally at 10. Machine 10 may be any of a variety of different machines adapted for cutting workpieces, such as wood, including a table saw, miter saw (chop saw), radial arm saw, circular saw, band saw, jointer, planer, etc. Machine 10 includes an operative structure 12 having a cutting tool 14 and a motor assembly 16 adapted to drive the cutting tool. Machine 10 also includes a safety system 18 configured to minimize the potential of a serious injury to a person using machine 10. Safety system 18 is adapted to detect the occurrence of one or more dangerous conditions during use of machine 10. If such a dangerous condition is detected, safety system 18 is adapted to engage operative structure 12 to limit any injury to the user caused by the dangerous condition.

Machine 10 also includes a suitable power source 20 to provide power to operative structure 12 and safety system 18. Power source 20 may be an external power source such as line current, or an internal power source such as a battery. Alternatively, power source 20 may include a combination of both external and internal power sources. Furthermore, power source 20 may include two or more separate power sources, each adapted to power different portions of machine 10.

It will be appreciated that operative structure 12 may take any one of many different forms, depending on the type of machine 10. For example, operative structure 12 may include a stationary housing configured to support motor assembly 16 in driving

engagement with cutting tool 14. Alternatively, operative structure 12 may include a movable structure configured to carry cutting tool 14 between multiple operating positions. As a further alternative, operative structure 12 may include one or more transport mechanisms adapted to convey a workpiece toward and/or away from cutting  
5 tool 14.

Motor assembly 16 includes one or more motors adapted to drive cutting tool 14. The motors may be either directly or indirectly coupled to the cutting tool, and may also be adapted to drive workpiece transport mechanisms. Cutting tool 14 typically includes one or more blades or other suitable cutting implements that are adapted to cut or remove  
10 portions from the workpieces. The particular form of cutting tool 14 will vary depending upon the various embodiments of machine 10. For example, in table saws, miter saws, circular saws and radial arm saws, cutting tool 14 will typically include one or more circular rotating blades having a plurality of teeth disposed along the perimetrical edge of the blade. For a jointer or planer, the cutting tool typically includes a plurality of radially  
15 spaced-apart blades. For a band saw, the cutting tool includes an elongate, circuitous tooth-edged band.

Safety system 18 includes a detection subsystem 22, a reaction subsystem 24 and a control subsystem 26. Control subsystem 26 may be adapted to receive inputs from a variety of sources including detection subsystem 22, reaction subsystem 24, operative  
20 structure 12 and motor assembly 16. The control subsystem may also include one or more sensors adapted to monitor selected parameters of machine 10. In addition, control subsystem 26 typically includes one or more instruments operable by a user to control the

machine. The control subsystem is configured to control machine 10 in response to the inputs it receives.

Detection subsystem 22 is configured to detect one or more dangerous, or triggering, conditions during use of machine 10. For example, the detection subsystem may be configured to detect that a portion of the user's body is dangerously close to, or in contact with, a portion of cutting tool 14. As another example, the detection subsystem may be configured to detect the rapid movement of a workpiece due to kickback by the cutting tool, such as is described in U.S. Provisional Patent Application Serial No. 60/182,866, filed February 16, 2000, and U.S. Patent No. 4,267,914, the disclosures of which are herein incorporated by reference. In some embodiments, detection subsystem 22 may inform control subsystem 26 of the dangerous condition, which then activates reaction subsystem 24. In other embodiments, the detection subsystem may be adapted to activate the reaction subsystem directly.

Once activated in response to a dangerous condition, reaction subsystem 24 is configured to engage operative structure 12 quickly to prevent serious injury to the user. It will be appreciated that the particular action to be taken by reaction subsystem 24 will vary depending on the type of machine 10 and/or the dangerous condition that is detected. For example, reaction subsystem 24 may be configured to do one or more of the following: stop the movement of cutting tool 14, disconnect motor assembly 16 from power source 20, place a barrier between the cutting tool and the user, or retract the cutting tool from its operating position, etc. The reaction subsystem may be configured to take a combination of steps to protect the user from serious injury. Placement of a barrier

between the cutting tool and teeth is described in more detail in U.S. Provisional Patent Application Serial No. 60/225,206, filed August 14, 2000, entitled "Cutting Tool Safety System," the disclosure of which is herein incorporated by reference. Retraction of the cutting tool from its operating position and/or the stopping of translational motion of the cutting tool are described in more detail in the following U.S. Provisional Patent Applications, all the disclosures of which are herein incorporated by reference: Serial No. 60/225,089, filed August 14, 2000, entitled "Retraction System For Use In Power Equipment," Serial No. 60/270,941, filed February 22, 2001, entitled "Power Saw with Improved Safety System," Serial No. 60/270,942, filed February 22, 2001, entitled "Miter Saw with Improved Safety System," Serial No. 60/273,177, filed March 2, 2001, entitled "Table Saw With Improved Safety System," Serial No. 60/273,178, filed March 2, 2001, entitled "Miter Saw with Improved Safety System," Serial No. 60/273,902, filed March 6, 2001, entitled "Miter Saw with Improved Safety System," Serial No. 60/275,594, filed March 13, 2001, entitled "Miter Saw with Improved Safety System," Serial No. 60/275,595, filed March 13, 2001, entitled "Safety Systems for Power Equipment," Serial No. 60/279,313, filed March 27, 2001, entitled "Miter Saw with Improved Safety System," and Serial No. 60/292,081, filed May 17, 2001, entitled "Translation Stop for Use in Power Equipment."

The configuration of reaction subsystem 24 typically will vary depending on which action(s) are taken. In the exemplary embodiment depicted in Fig. 1, reaction subsystem 24 is configured to stop the movement of cutting tool 14 and includes a brake mechanism 28, a biasing mechanism 30, a restraining mechanism 32, and a release

mechanism 34. Brake mechanism 28 is adapted to engage operative structure 12 under the urging of biasing mechanism 30. During normal operation of machine 10, restraining mechanism 32 holds the brake mechanism out of engagement with the operative structure. However, upon receipt of an activation signal by reaction subsystem 24, the  
5 brake mechanism is released from the restraining mechanism by release mechanism 34, whereupon, the brake mechanism quickly engages at least a portion of the operative structure to bring the cutting tool to a stop.

It will be appreciated by those of skill in the art that the exemplary embodiment depicted in Fig. 1 and described above may be implemented in a variety of ways  
10 depending on the type and configuration of operative structure 12. Turning attention to Fig. 2, one example of the many possible implementations of safety system 18 is shown. System 18 is configured to engage an operative structure having a cutting tool in the form of a circular blade 40 mounted on a rotating shaft or arbor 42. Blade 40 includes a plurality of cutting teeth (not shown) disposed around the outer edge of the blade. As  
15 described in more detail below, braking mechanism 28 is adapted to engage the teeth of blade 40 and stop the rotation of the blade. U.S. Provisional Patent Application Serial No. 60/225,210, filed August 14, 2000, entitled "Translation Stop For Use In Power Equipment," and U.S. Provisional Patent Application Serial No. 60/233,459, filed September 18, 2000, entitled "Translation Stop For Use In Power Equipment," the  
20 disclosures of which are herein incorporated by reference, describe other systems for stopping the movement of the cutting tool. Although the embodiment depicted in Figs. 1 and 2 schematically illustrate machine 10 as a generic woodworking machine, it will be

appreciated that safety system 18 may be incorporated into virtually any specific type of woodworking machine. For example, the following U.S. Provisional Patent Applications, the disclosures of which are herein incorporated by reference, describe safety system 18 in the context of various specific types of machines such as table saws, miter saws, radial arm saws, band saws, pneumatic up-cut saws, routers, etc.: U.S. Provisional Patent Application Serial No. 60/225,058, filed August 14, 2000, entitled "Table Saw With Improved Safety System," U.S. Provisional Patent Application Serial No. 60/225,057, filed August 14, 2000, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Serial No. 60/233,459, filed September 18, 2000, entitled "Translation Stop For Use In Power Equipment," U.S. Provisional Patent Application Serial No. 60/270,941, filed February 22, 2001, entitled "Power Saw With Improved Safety System," U.S. Provisional Patent Application Serial No. 60/270,942, filed February 22, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Serial No. 60/273,177, filed March 2, 2001, entitled "Table Saw With Improved Safety System," U.S. Provisional Patent Application Serial No. 60/273,178, filed March 2, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Serial No. 60/273,902, filed March 6, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Serial No. 60/275,594, filed March 13, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Serial No. 60/275,595, filed March 13, 2001, entitled "Safety Systems For Power Equipment," U.S. Provisional Patent Application Serial No. 60/279,313, filed March 27, 2001, entitled "Miter Saw

With Improved Safety System,” U.S. Provisional Patent Application Serial No. 60/292,081, filed May 17, 2001, entitled “Translation Stop For Use In Power Equipment,” U.S. Provisional Patent Application Serial No. 60/292,100, filed May 17, 2001, entitled “Band Saw with Improved Safety System,” U.S. Provisional Patent Application Serial No. 60/298,207, filed June 13, 2001, entitled “Apparatus And Method For Detecting Dangerous Conditions In Power Equipment,” and U.S. Provisional Patent Application Serial No. 60/306,202, filed July 18, 2001, entitled “Router With Improved Safety System.”

In the exemplary implementation, detection subsystem 22 is adapted to detect the dangerous condition of the user coming into contact with blade 40. The detection subsystem includes a sensor assembly, such as contact detection plates 44 and 46, configured to detect any contact between the user’s body and the blade. The detection subsystem is adapted to transmit a signal to control subsystem 26 when contact between the user and the blade is detected. Various exemplary embodiments and implementations of detection subsystem 22 are described in more detail in U.S. Provisional Patent Application Serial No. 60/225,200, filed August 14, 2000, entitled “Contact Detection System For Power Equipment,” U.S. Provisional Patent Application Serial No. 60/225,211, filed August 14, 2000, entitled “Apparatus And Method For Detecting Dangerous Conditions In Power Equipment,” U.S. Provisional Patent Application Serial No. 60/270,011, filed February 20, 2001, entitled “Contact Detection System for Power Equipment,” U.S. Provisional Patent Application Serial No. 60/292,100, filed May 17, 2001, entitled “Band Saw With Improved Safety System,” U.S. Provisional

Patent Application Serial No. 60/298,207, filed June 13, 2001, entitled "Apparatus And Method For Detecting Dangerous Conditions In Power Equipment," and U.S. Provisional Patent Application Serial No. 60/302,937, filed July 2, 2001, entitled "Discrete Proximity Detection System," the disclosures of which are herein incorporated by reference.

5           Control subsystem 26 includes one or more instruments 48 that are operable by a user to control the motion of blade 40. Instruments 48 may include start/stop switches, speed controls, direction controls, etc. Control subsystem 26 also includes a logic controller 50 connected to receive the user's inputs via instruments 48. Logic controller 50 is also connected to receive a contact detection signal from detection subsystem 22.

10       Further, the logic controller may be configured to receive inputs from other sources (not shown) such as blade motion sensors, workpiece sensors, etc. In any event, the logic controller is configured to control operative structure 12 in response to the user's inputs through instruments 48. However, upon receipt of a contact detection signal from

15       detection subsystem 22, the logic controller overrides the control inputs from the user and activates reaction subsystem 24 to stop the motion of the blade. Various exemplary embodiments and implementations of control subsystem 26 are described in more detail in U.S. Provisional Patent Application Serial No. 60/225,059, filed August 14, 2000, entitled "Logic Control For Fast Acting Safety System," and U.S. Provisional Patent

20       Application Serial No. 60/225,094, filed August 14, 2000, entitled "Motion Detecting System For Use In Safety System For Power Equipment," the disclosures of which are herein incorporated by reference.

In the exemplary implementation, brake mechanism 28 includes a pawl 60 mounted adjacent the edge of blade 40 and selectively moveable to engage and grip the teeth of the blade. Pawl 60 may be constructed of any suitable material adapted to engage and stop the blade. As one example, the pawl may be constructed of a relatively high strength thermoplastic material such as polycarbonate, ultrahigh molecular weight polyethylene (UHMW) or Acrylonitrile Butadiene Styrene (ABS), etc., or a metal such as aluminum, etc. It will be appreciated that the construction of pawl 60 will vary depending on the configuration of blade 40. In any event, the pawl is urged into the blade by a biasing mechanism in the form of a spring 66. In the illustrative embodiment shown in Fig. 2, pawl 60 is pivoted into the teeth of blade 40. It should be understood that sliding or rotary movement of pawl 60 may also be used. The spring is adapted to urge pawl 60 into the teeth of the blade with sufficient force to grip the blade and quickly bring it to a stop.

The pawl is held away from the edge of the blade by a restraining mechanism in the form of a fusible member 70. The fusible member is constructed of a suitable material adapted to restrain the pawl against the bias of spring 66, and also adapted to melt under a determined electrical current density. Examples of suitable materials for fusible member 70 include NiChrome wire, stainless steel wire, etc. The fusible member is connected between the pawl and a contact mount 72. Preferably member 70 holds the pawl relatively close to the edge of the blade to reduce the distance the pawl must travel to engage the blade. Positioning the pawl relatively close to the edge of the blade reduces the time required for the pawl to engage and stop the blade. Typically, the pawl is held

approximately 1/32-inch to 1/4-inch from the edge of the blade by fusible member 70, however other pawl-to-blade spacings may also be used within the scope of the invention.

Pawl 60 is released from its unactuated, or cocked, position to engage blade 40 by a release mechanism in the form of a firing subsystem 76. The firing subsystem is coupled to contact mount 72, and is configured to melt fusible member 70 by passing a surge of electrical current through the fusible member. Firing subsystem 76 is coupled to logic controller 50 and activated by a signal from the logic controller. When the logic controller receives a contact detection signal from detection subsystem 22, the logic controller sends an activation signal to firing subsystem 76, which melts fusible member 70, thereby releasing the pawl to stop the blade. Various exemplary embodiments and implementations of reaction subsystem 24 are described in more detail in U.S. Provisional Patent Application Serial No. 60/225,056, filed August 14, 2000, entitled "Firing Subsystem For Use In Fast Acting Safety System," U.S. Provisional Patent Application Serial No. 60/225,170, filed August 14, 2000, entitled "Spring-Biased Brake Mechanism for Power Equipment," and U.S. Provisional Patent Application Serial No. 60/225,169, filed August 14, 2000, entitled "Brake Mechanism For Power Equipment," U.S. Provisional Patent Application Serial No. 60/279,313, filed March 27, 2001, entitled "Miter Saw With Improved Safety System," U.S. Provisional Patent Application Serial No. 60/292,081, filed May 17, 2001, entitled "Translation Stop For Use In Power Equipment," U.S. Provisional Patent Application Serial No. 60/292,100, filed May 17, 2001, entitled "Band Saw With Improved Safety System," U.S. Provisional Patent Application Serial No. 60/302,916, filed July 3, 2001, entitled

“Actuators For Use With Fast-Acting Safety Systems,” and U.S. Provisional Patent Application Serial No. 60/307,756, filed July 25, 2001, entitled “Actuators For Use With Fast-Acting Safety Systems,” the disclosures of which are herein incorporated by reference.

5           It will be appreciated that activation of the brake mechanism will require the replacement of one or more portions of safety system 18. For example, pawl 60 and fusible member 70 typically must be replaced before the safety system is ready to be used again. Thus, it may be desirable to construct one or more portions of safety system 18 in a cartridge that can be easily replaced. For example, in the exemplary implementation  
10 depicted in Fig. 2, safety system 18 includes a replaceable cartridge 80 having a housing 82. Pawl 60, spring 66, fusible member 70 and contact mount 72 are all mounted within housing 82. Alternatively, other portions of safety system 18 may be mounted within the housing. In any event, after the reaction system has been activated, the safety system can be reset by replacing cartridge 80. The portions of safety system 18 not mounted within  
15 the cartridge may be replaced separately or reused as appropriate. Various exemplary embodiments and implementations of a safety system using a replaceable cartridge are described in more detail in U.S. Provisional Patent Application Serial No. 60/225,201, filed August 14, 2000, entitled “Replaceable Brake Mechanism For Power Equipment,” U.S. Provisional Patent Application Serial No. 60/225,212, filed August 14, 2000,  
20 entitled “Brake Positioning System,” U.S. Provisional Patent Application Serial No. 60/279,313, filed March 27, 2001, entitled “Miter Saw With Improved Safety System,” U.S. Provisional Patent Application Serial No. 60/306,202, filed July 18, 2001,

entitled "Router With Improved Safety System," U.S. Provisional Patent Application Serial No. 60/302,916, filed July 3, 2001, entitled "Actuators For Use With Fast-Acting Safety Systems," and U.S. Provisional Patent Application Serial No. 60/307,756, filed July 25, 2001, entitled "Actuators For Use With Fast-Acting Safety Systems," the disclosures of which are herein incorporated by reference.

Additional variations and modifications of safety system 18 are described in U.S. Provisional Patent Application Serial Nos. 60/182,866, filed February 16, 2000, and 60/157,340, filed October 1, 1999, both entitled "Fast-Acting Safety Stop," the disclosures of which are herein incorporated by reference.

It is believed that the disclosure set forth above encompasses multiple distinct inventions with independent utility. While each of these inventions has been disclosed in its preferred form, the specific embodiments thereof as disclosed and illustrated herein are not to be considered in a limiting sense as numerous variations are possible. The subject matter of the inventions includes all novel and non-obvious combinations and sub-combinations of the various elements, features, functions and/or properties disclosed herein. No single feature, function, element or property of the disclosed embodiments is essential to all of the disclosed inventions. Similarly, where the claims recite "a" or "a first" element or the equivalent thereof, such claims should be understood to include incorporation of one or more such elements, neither requiring nor excluding two or more such elements.

It is believed that the following claims particularly point out certain combinations and sub-combinations that are directed to one of the disclosed inventions and are novel

and non-obvious. Inventions embodied in other combinations and sub-combinations of features, functions, elements and/or properties may be claimed through amendment of the present claims or presentation of new claims in this or a related application. Such amended or new claims, whether they are directed to a different invention or directed to  
5 the same invention, whether different, broader, narrower or equal in scope to the original claims, are also regarded as included within the subject matter of the inventions of the present disclosure.